

# Multimatic® 220 AC/DC

MIG, Stick and  
AC/DC TIG Package



## QUICK SPECS

### Light Industrial Applications

Light fabrication  
Maintenance and repair  
Auto body  
Farm/home

### Processes

MIG (GMAW)  
Flux-cored (FCAW)  
DC stick (SMAW)  
AC/DC TIG (GTAW)  
Pulsed TIG (GTAW-P)

**Input Power** 120/240 V, single-phase, 50/60 Hz

**Amperage Range** **MIG:** 30–230 A  
**DC Stick:** 30–200 A  
**AC/DC TIG:** 20–210 A

**Net Weight** 56 lb. (25.4 kg)

## The Multimatic 220 AC/DC. It does... so you can too.

Ideal for hobbyists and small shops, the Multimatic 220 AC/DC gives you the freedom to weld any process — MIG, flux-cored, stick and AC/DC TIG — with one portable, powerful, easy-to-use machine. Setup and switching processes are fast and easy, all while ensuring excellent arc quality using either 120- or 240-volt power.



Multiple processes  
with only one machine



Auto polarity,  
process and settings



Quick and easy setup



Light enough to easily  
move around a shop

### Comes complete with:

- Power source
- 10 ft. (3 m) MDX™-100 MIG gun
- 13 ft. (4 m) cable with electrode holder and 25 mm Dinse-style connector
- 12.5 ft. (3.8 m) Weldcraft™ A-150 (WP-17) TIG torch with 25 mm Dinse-style connector
- 10 ft. (3 m) work cable with clamp and 25 mm Dinse-style connector
- 6.5 ft. (2 m) power cord with MVP™ plugs for 120 V and 240 V
- RFCS-14 HD foot control with 20 ft. (6 m) cord **OR** wireless foot control
- Two flow gauge regulators and gas hoses for argon or AR/CO<sub>2</sub> mix
- Hobart® spool of .030 in. (0.8 mm) solid wire
- Two contact tips for .030 in. (0.8 mm) wire
- Quick Select™ drive roll for .024 in. (0.6 mm) or .030/.035 in. (0.8/0.9 mm) solid wire, and .030/.035 in. (0.8/0.9 mm) flux-cored wire
- AK2C TIG torch accessory kit
- Hook-and-loop cord wraps
- Material thickness gauge ▶ 229895

*Note: Shielding gas and safety equipment not included.*



Welder is warranted for three years, parts and labor.  
Gun warranted for 90 days, parts only.



Miller Electric Mfg. LLC  
An ITW Welding Company  
1635 West Spencer Street  
P.O. Box 1079  
Appleton, WI 54912-1079 USA

Equipment Sales US and Canada  
Phone: 866-931-9730  
International Phone: 920-735-4554

MillerWelds.com



# Multimatic® 220 AC/DC Features and Benefits

## All in One



Take on more projects with one machine that has MIG, DC stick and AC/DC TIG.

MIG: 24 ga.–3/8 in. steel

18 ga.–3/8 in. aluminum

DC stick: 16 ga.–3/8 in. steel

AC/DC TIG: 24 ga.–1/4 in. steel and aluminum


## Easy to Use



**Innovative QuickTech™ makes setup and changing processes easy.**

- Automatically determines the polarity. Work is always connected to the bottom right receptacle. MIG gun and TIG torch can stay connected at the same time.

- Automatically switches to the right process. Just hit the trigger or the foot control and the machine automatically changes, eliminating the need to manually change processes.
- Automatically recalls the settings from the last process used.



**Auto-Set™** offers predefined weld settings to increase ease of use and ensure that the job is done right for operators of all skill levels.

- Available for MIG, stick and AC/DC TIG processes with the ability to fine-tune your settings.
- Set weld parameters by selecting:
  - MIG (shown) — wire diameter and material thickness
  - Stick — electrode type, electrode diameter and material thickness
  - AC/DC TIG — tungsten diameter and material thickness

### MDX™-100 MIG gun with MDX™ MIG gun consumables

features a dual-locked, front-loading liner that optimizes wire feedability.

- Coarse threads on MDX contact tips speed up tip replacement.
- Front load liner locks at front and back of gun to align with contact tip and power pin for a flawless wire feed path.
- Durable, ergonomic handle with overmolding improves grip and comfort.
- Ball-and-socket handle with rear swivel for increased gun maneuverability while reducing welder fatigue.



**Pro-Set™ (stick and TIG manual modes)**

eliminates the guesswork when setting weld parameters. Simply adjust control until Pro-Set appears on the display and the number turns blue.

- DIG (Stick) — lets you tailor arc characteristics for a wide range of applications (Pro-Set 30% 7018 electrodes)
- AC Balance (AC TIG) — controls the cleaning action (Pro-Set 75%)
- AC Frequency (AC TIG) — controls the width of the arc cone (Pro-Set 120 Hz)
- Pulse (DC TIG) — helps focus the arc for increased stability, penetration and travel speed (Pro-Set 100 Hz)




**Robust, angled wire drive with**

**Quick Select™ drive roll** for easily changing one wire type/diameter to another. Quick Select drive roll offers three grooves — two for different size solid wires and a third for flux-cored wire.



**Two shielding gas connections**

**(one for MIG and one for TIG)** so both gases can be left connected to the machine — no switching needed.



**3.5-inch color LCD display** with easy-to-understand interface and intuitive connection setup images.

# Multimatic® 220 AC/DC Features and Benefits

## Versatility



**Operates on 120-volt or 240-volt power** letting you work virtually anywhere. Multi-voltage plug (MVP™) easily connects to common 120-volt or 240-volt power outlets — no tools required. Choose the plug that fits the receptacle and connect it to the power cord.



Optional wireless foot control shown.

**14-pin controlled operator alternatives.** The standard 14-pin connector on your Multimatic 220 AC/DC lets you choose your control for a customized experience, whether it's a foot control, fingertip control, or wireless foot control.

*Note: Multimatic 220 AC/DC is not compatible with wireless hand control.*



**Generator compatible.** The Multimatic 220 AC/DC will be able to operate and provide full output when powered by generators with 10,000-watt (10 kW) output or higher, such as a Miller Bobcat™ or Trailblazer® series generator. Limited output will occur when used with smaller generators.



### Wide range of TIG adjustability.

- AC balance — adjustable from 60–80%
- AC frequency — adjustable from 60–150 Hz
- DC pulse — adjustable from Off–150 pulses per second (PPS)
- TIG postflow — adjustable from Auto–25 seconds (accessible through service menu screen 12)
- Lift-Arc™ and high-frequency starts
- Tungsten size selection

## Portability



**Weighing only 56 pounds**, the Multimatic 220 AC/DC can go where the work is, plus the added convenience of one machine versus two or more.

**Optional dual cylinder rack cart** offers portability while holding two gas cylinders.



# Specifications (Subject to change without notice.)






WELDING MODE/PROCESS	INPUT POWER	WELDING AMPERAGE RANGE	RATED OUTPUT	AMPS INPUT AT RATED OUTPUT, 50/60 HZ				WIRE FEED SPEED	MAX. OPEN-CIRCUIT VOLTAGE	DIMENSIONS	NET WEIGHT
				120 V	240 V	KVA	KW				
CV: MIG/flux-cored	120 V	30–125 A	105 A at 19.2 V, 60% duty cycle	23.3	—	2.8	2.8	60–600 ipm (1.5–15.2 m/min.)	45 VDC	H: 17.5 in. (445 mm) W: 11.25 in. (286 mm) D: 21.5 in. (546 mm)	56 lb. (25.3 kg)
	240 V	30–230 A	200 A at 24 V, 20% duty cycle	—	27.2	4.8	4.8				
			170 A at 21.5 V, 40% duty cycle	—	21.5	3.8	3.8				
CC: Stick*	120 V	30–90 A	90 A at 23.6 V, 40% duty cycle	24.5	—	2.9	2.9	—	46 VDC		
	240 V	30–200 A	200 A at 28.4 V, 15% duty cycle	—	31.3	7.5	7.5				
CC: TIG	120 V	20–140 A	130 A at 15.2 V, 40% duty cycle	24.0	—	2.9	2.9				
	240 V	20–210 A	210 A at 18.4 V, 20% duty cycle	—	22.4	5.4	5.4				



\*Superior stick arc performance even on the difficult-to-run electrodes like E6010.

Certified by Canadian Standards Association to both the Canadian and U.S. Standards.

## Performance Data



# Control Panel



1. Material Thickness Buttons
2. Auto-Set™ Button
3. Wire/Rod/Tungsten Buttons
4. Color LCD Display
5. Process Buttons
6. Adjustment Knobs


7. TIG Arc Start Buttons  
*(Lift-Arc™ not available for TIG aluminum)*
8. Plastic Hub with Retaining Ring for 8-inch Spools  
*(shaft also accepts 4-inch spools)*

9. Calibrated Tension Knob
10. Drive Roll
11. Gun Securing Knob
12. Four-pin Trigger Control Cable Receptacle

Note: Power switch and gas solenoid are on power source rear panel.

## TIG Aluminum Manual Mode


Note: Button and knob functions change in TIG manual modes from the main panel above.



1. Balance Adjustment Buttons (*Pro-Set™ 75%*)
2. Tungsten Size Buttons
3. Frequency Adjustment Knob (*Pro-Set™ 120 Hz*)
4. Amperage Adjustment Knob
5. TIG Arc Start Buttons  
*(Lift-Arc™ not available for TIG aluminum)*

## TIG Steel/Stainless Manual Mode

Note: Button and knob functions change in TIG manual modes from the main panel above.



1. Tungsten Size Buttons
2. Pulse Adjustment Knob (*Pro-Set™ 100 pps*)
3. Amperage Adjustment Knob
4. TIG Arc Start Buttons

# Genuine Miller® Accessories



**MDX™-100 MIG Gun 1770028**  
100-amp MIG gun with MDX™ consumables for .030–.035 in. (0.8–0.9 mm) wire. Includes 10 ft. (3 m) cable assembly.



**Spoolmate™ 100 Spool Gun 300371**  
Direct-connect spool gun handles .030–.035 inch (0.8–0.9 mm) aluminum (4043 only) and .023–.035 inch (0.6–0.9 mm) steel/stainless steel wires. Rated at 135 amps, 30 percent duty cycle. Includes 12-foot (3.7 m) cable assembly and custom carrying case.



**Spoolmate™ 150 Spool Gun 301272**  
Direct-connect spool gun handles .030–.035 inch (0.8–0.9 mm) 4000/5000 series aluminum and .023–.035 inch (0.6–0.9 mm) steel/stainless steel wires. Rated at 150 amps, 60 percent duty cycle. Includes 20-foot (6.1 m) cable assembly.



**Weldcraft™ A-150 (WP-17) TIG Torch WP1712RDI25**  
12.5-foot (3.8 m) 150-amp air-cooled torch with 25 mm flow thru Dinse-style connector.



**TIG Torch Accessory Kit AK2C**  
Includes one short back cap, one of each size (#4, #5, #6) alumina nozzle, and one of each size (.040, 1/16, 3/32 inch) of the following: collet, collet body, and 7-inch 2% ceriated tungsten electrode.



**TIG Torch Accessory Kit AK-150MFC**  
Allows welding operators to customize their standard Weldcraft™ A-150 (WP-17) TIG torch

for their specific application. Kit converts into 28 different torch styles while using the existing cable. Features nozzles, collets, collet bodies, torch heads, handle and more.



**Coolmate™ 1S 301856**  
120/240-volt, 1-phase, 50/60 Hz. 1.0-gallon cooler designed to cool

torches up to 250 amps. Requires 25 mm flow thru Dinse for water cooler **301883**.



**Low-Conductivity Coolant 043810**  
Must be ordered in quantities of four. One-gallon recyclable plastic bottle. Miller coolants contain a base of ethylene glycol and

deionized water to protect against freezing to -37 degrees Fahrenheit (-38°C) or boiling to 227 degrees Fahrenheit (108°C).



**Protective Cover 301524**



**Dual Cylinder Rack Cart 951770**  
Package consists of both running gear/cylinder rack 301239 and dual cylinder rack conversion kit 301454. Cart features durable construction with rubber rear wheels, convenient front handles, cable holders, plastic consumable box, and dual cylinder rack with tool holder. Holds two cylinders, each gas cylinder should be no greater than 7 inches (178 mm) in diameter or 65 pounds (29.5 kg) in weight.

## MVP™ Plugs



**219258**  
For power cable 6-50P (240 V/50 A). Included with machine.



**219261**  
For power cable 5-15P (120 V/15 A). Included with machine.



**219259**  
For power cable 5-20P (120 V/20 A). Optional, not included with machine.

## Remote Controls



**Wireless Remote Foot Control 301580**  
For remote current and contactor control. Receiver plugs directly into the 14-pin receptacle of Miller machine. 90-foot (27.4 m) operating range.

*Note: Multimatic 220 AC/DC is not compatible with wireless hand control.*



**RFCS-14 HD Foot Control 301589**  
Heavy-duty foot pedal current and contactor control provides increased stability and durability from larger base

and heavier cord. Includes 20-foot (6 m) cord with plug.



**RCC-14 Remote Contactor and Current Control 151086**  
East/west rotary-motion fingertip control attaches to TIG torch using two hook-and-loop fasteners. Includes 26.5-foot (8 m) cord with 14-pin plug.



**RCCS-14 Remote Contactor and Current Control 043688**  
North/south rotary-motion fingertip control attaches to TIG torch using two hook-and-loop fasteners. Includes 26.5-foot (8 m) cord with 14-pin plug.

# Consumables

## For MDX™-100 MIG Gun

### MDX MIG Gun Consumables

Smaller consumables and components to access hard-to-reach weldments.

### Contact Tips (10 per package)

**T-M023** .023 in. (0.6 mm)  
**T-M030** .030 in. (0.8 mm)  
**T-M035** .035 in. (0.9 mm)  
**T-M045** .045 in. (1.2 mm)  
**T-M047** 3/64 in. (1.2 mm)

### Nozzles

**NS-M1200B** Brass, 1/2 in. ID, flush  
**NS-M1200C** Copper, 1/2 in. ID, flush  
**NS-MFLX** Gasless nozzle

### Diffuser D-M100

### Monocoil Replacement Liners (10 ft.)

**LM1A-10** .023/.025 in. (0.6 mm)  
**LMD2A-10** .030/.035 in. (0.8/0.9 mm)  
**LMD3A-10** .035/.045 in. (0.9/1.2 mm)

*Note: Miller® FasTip™, M-Series and Bernard® Centerfire™ diffusers and consumables are NOT compatible with MDX Series guns.*

## For Spoolmate™ 100 Spool Gun



### Contact Tips (5 per package)

**199730** .024 in. (0.6 mm)  
**186419** .030 in. (0.8 mm)  
**186406** .035 in. (0.9 mm)




Nozzle 186405

## For Spoolmate™ 150 Spool Gun



### Contact Tips (5 per package)

**199387** .030 in. (0.8 mm)  
**199388** .035 in. (0.9 mm)



Nozzle 050622

## For Both Spool Guns



**Drive Roll (1) 186413**  
For .030/.035-inch (0.8/0.9 mm) wire.



**Push Roll (1) 186414**  
For .030/.035-inch (0.8/0.9 mm) wire.

## For Multimatic® 215 PRO



### Quick Select™ Drive Roll 261157

For .024-inch (0.6 mm) or .030/.035-inch (0.8/0.9 mm) solid wire, and .030/.035-inch (0.8/0.9 mm) flux-cored wire.

**V-Knurled Dual-Groove Drive Roll 202926**  
For .030/.035-inch (0.8/0.9 mm) or .045-inch (1.2 mm) flux-cored wire.

# Ordering Information

EQUIPMENT AND OPTIONS	STOCK NO.	DESCRIPTION	QTY.	PRICE
<b>Multimatic® 220 AC/DC</b>	<b>907757</b>	120/240 V, 50/60 Hz with RFCS-14 HD foot control		
	<b>907757002</b>	120/240 V, 50/60 Hz with wireless foot control		
<b>Multimatic® 220 AC/DC with Cart</b>	<b>951000070</b>	Includes Multimatic® 220 AC/DC (907757) and dual cylinder rack cart (951770)		
	<b>951000104</b>	Includes Multimatic® 220 AC/DC (907757002) and dual cylinder rack cart (951770)		
<b>Guns</b>				
MDX™-100 MIG Gun with MDX™ Consumables	<b>1770028</b>	10 ft. (3 m), 100 A, .030-.035 in. (0.8-0.9 mm) wire		
Spoolmate™ 100 Spool Gun	<b>300371</b>	12 ft. (3.7 m). Includes custom carrying case		
Spoolmate™ 150 Spool Gun	<b>301272</b>	20 ft. (6.1 m)		
<b>Accessories</b>				
Weldcraft™ A-150 (WP-17) TIG Torch	<b>WP1712RDI25</b>	12.5 ft. (3.8 m) cable		
TIG Torch Accessory Kits	<b>AK2C</b>	For use with Weldcraft™ A-150 (WP-17) Torch		
	<b>AK-150MFC</b>	For use with Weldcraft™ A-150 (WP-17) Torch		
Coolmate™ 1S	<b>301856</b>	120/240-volt, 1-phase, 50/60 Hz. <i>Requires 25 mm flow thru Dinse and coolant</i>		
25 mm Flow Thru Dinse for Water Cooler	<b>301883</b>	Required for Multimatic 220 AC/DC use with Coolmate 1S		
TIG Coolant (must be ordered in quantities of four)	<b>043810</b>	1-gallon plastic bottle. Protects against freezing to -37° Fahrenheit (-38°C) or boiling to 227° Fahrenheit (108°C)		
Protective Cover	<b>301524</b>			
Dual Cylinder Rack Cart	<b>951770</b>	Includes running gear/cylinder rack 301239 and dual cylinder rack conversion kit 301454. Must be assembled together		
MVP™ Plugs		See page 6		
Material Thickness Gauge	<b>229895</b>			
Replacement Screen Cover	<b>271493</b>	Replacement cover for LCD display panel		
Flow Gauge Regulator for Argon or AR/CO <sub>2</sub> Mix	<b>31-50-580-6</b>	Replacement standard regulator		
Flow Gauge Regulator for CO <sub>2</sub>	<b>31-50-320</b>	Required if using 100 percent CO <sub>2</sub> gas		
Extended Power Pin	<b>214-6-116</b>	Required if using a Bernard® BTB MIG gun		
<b>Remote Controls</b>				
Wireless Remote Foot Control	<b>301580</b>	Foot control with wireless 90 ft. (27.4 m) operating range		
RFCS-14 HD	<b>301589</b>	Heavy-duty foot control (included with TIG kit and TIG package)		
RCC-14	<b>151086</b>	Fingertip control		
RCCS-14	<b>043688</b>	Fingertip control		
<b>Consumables</b>				
Contact Tips		See page 7		
Nozzles		See page 7		
Diffuser		See page 7		
Monocoil Replacement Liners		See page 7		
Drive Rolls		See page 7		

DATE :

TOTAL QUOTED PRICE:

Distributed by:

