



INQUIRE ABOUT THIS PRODUCT

BUY NOW

## HRF 2400 SERIES FLOW METER

[OVERVIEW](#)

[DOCUMENTS AND SPECS](#)

[ORDERING INFORMATION](#)



HRF 2400 series regulator/flowmeter combination are specially designed for MIG, TIG, and other inert gas welding applications. Unique design and construction features make these units equally suited for applications from the industrial jobsite to the laboratory.

### Features

Designed for CO<sub>2</sub> application (non-siphoned tube cylinders)

High flow CO<sub>2</sub> applications (SR 310 100 PSIG) (SR 311/312 100 SCFH) with adequate supply or source

Designed for core wire applications

Machined aluminum body & housing cap

2" (50.8 mm) gauge

Stem type seat mechanism

1.75" (44.5 mm) diaphragm - fabric reinforced neoprene

Self reseating relief valve (not designed to protect downstream equipment)

Sintered inlet filter - bronze

A regulator equipped with a flow gauge is not accurate when a back pressure in excess of 2 PSIG exists at the outlet. Back pressure is caused by a restriction in the equipment downstream of the flow gauge. Metering valves, kinked hoses or even very long hoses are restrictions that can cause back pressure. In applications where back pressure in excess of 2 PSIG can be expected, a regulator equipped with a flow meter should be used. **WARNING:** High gas withdrawal rates may cause regulator freeze up and will require cylinder manifolding. Consult your gas supplier

## **Industries**

Industrial and General Fabrication

Structural Steel Fabrication

Repair and Maintenance

Light Fabrication